




METHOD FOR MANUFACTURING NITRIDE SEMICONDUCTOR, METHOD FOR MANUFACTURING NITRIDE SEMICONDUCTOR ELEMENT AND NITRIDE SEMICONDUCTOR ELEMENT USING THE SAME

Patent number: JP2002198314
Publication date: 2002-07-12
Inventor: ISHIBASHI AKIHIKO; TSUJIMURA AYUMI;
 HASEGAWA YOSHITERU; OTSUKA NOBUYUKI;
 SUGAWARA TAKESHI; MIYANAGA RYOKO;
 SHIMAMOTO TOSHITAKA; FUKUTO KENJI; BAN
 YUZABURO; ONAKA SEIJI
Applicant: MATSUSHITA ELECTRIC IND CO LTD
Classification:
 - international: **H01L21/205; H01L33/00; H01L21/02; H01L33/00;**
 (IPC1-7): H01L21/205; H01S5/323
 - european: H01L21/205C6; H01L33/00G3B2
Application number: JP20000392003 20001225
Priority number(s): JP20000392003 20001225

Also published as:


 EP1220304 (A2)
 US6586774 (B2)
 US2002081763 (A1)

Best Available Copy

Report a data error here

Abstract of JP2002198314

PROBLEM TO BE SOLVED: To obtain a sharp p type impurity profile with low resistance by increasing p type impurity concentration of a nitride semiconductor without increasing the doping quantity. **SOLUTION:** An MQW active layer 19 and a p type super lattice cap layer 20 formed on the MQW active layer 19 are formed on a substrate 11. The p type super lattice cap layer 20 is comprised of four-cycle-laminate of a first layer 20a which is a GaN and a second layer 20b which is an AlGaIn formed on the first layer 20a. The concentration of the p type dopant increases locally at an adjacent region to a boundary face between the first layer 20a and the second layer 20b.



Data supplied from the esp@cenet database - Worldwide